

# SALONI

## anti-reflective interior paint

**Sempre**<sup>®</sup>

### PROPERTIES:

- anti-reflective
- uniformly deep matte
- streak-free coating
- perfectly flowing
- drip-free painting
- wide range of colors

### APPLICATION

**SALONI** is a new generation paint for painting walls and ceilings in bright rooms with high levels of natural and artificial light. The low angle of light reflection from the paint film gives wall surfaces a uniformly matte appearance, without visible streaks. It is ideal for covering walls with visible imperfections. Its extended open time and excellent flow create a smooth, uniform, matte finish. Furthermore, the non-drip formula is user-friendly. Recommended for interior painting of rooms made of typical mineral materials such as limestone, lime-cement plasters, gypsum plaster, plasterboard, etc., as well as those covered with other paint coatings. It is intended for decorative and protective coatings in bedrooms, living rooms, children's rooms, living rooms, hallways, offices, kitchens, public spaces, and hospitals. Available in colors matching the IMPRESSIO and TUSCANY color ranges, or dyed based on a provided sample. It has a Hygiene Certificate issued by the National Institute of Public Health – National Institute of Hygiene (PZH).

### TECHNICAL DATA

|                           |  |
|---------------------------|--|
| <b>Group of products</b>  | Products for interior  |
| <b>Contains</b>           | acrylic dispersion, titanic dioxide, calcium carbonate, water, preservatives, additives.                     |
| <b>Colors</b>             | White and in colour in accordance with the IMPRESSIO, TOSKANIA COLOURS and according to the design provided. |
| <b>Coating appearance</b> | Dead-Matt  |
| <b>Consumption</b>        | ca. 0,12 l/m <sup>2</sup> for single painting, depending on the absorbency of the substrate *                |

| PARAMETERS | Parameter   | Norm               | Value                         | Unit                      |
|------------|---|--------------------|-------------------------------|---------------------------|
|            | Density   | EN ISO 2811-1:2023 | 1,40 – 1,50                   | g/cm <sup>3</sup>         |
|            | Appearance of the coating / specular gloss  | EN 13300:2022      | Matt/<br>G4 ( $\leq$ 5)       | ---                       |
|            | Largest grain size (granularity)  | EN 13300:2022      | S1 (fine - $\leq$ 100)        | $\mu$ m                   |
|            | Wet scrub resistance (at 200 scrubs)  | EN 13300:2022      | Class R2 ( $>$ 5 - $\leq$ 20) | $\mu$ m                   |
|            | Water vapor transmission rate V/ S <sub>d</sub>   | EN ISO 7783:2018   | V <sub>1</sub> / < 0,14       | g/(m <sup>2</sup> · d)/ m |
|            | Hiding power  | EN 13300:2022      | H10 Class 1                   | -                         |
|            | VOC content limit according to Directive 2004/42 /EC for this product: Cat. A/a/WB limit value: 30 g/l.<br>This product contains max 30 g/l |                    |                               |                           |

The values stated are average values obtained during testing. Due to the use of natural resources actual values may differ slightly from those listed in the table.

\* Consumption is dependent on substrate and application technique. The stated value is an estimate.

### USE INSTRUCTION

|                   |   |
|-------------------|---|
| <b>Substrates</b> | Typical construction substrate should be clean, firm, sound, even and free of grease. Loose grain and pollution, and poorly linked to the old emulsion paint coatings must be carefully removed. Any irregularities and defects should be supplemented with finishing filler or adequate mortar (e.g. ACRYL SPACHTEL, BUDOMONT ZT-620 or ZS-640). Surfaces infected with fungus and algae |
|-------------------|---|

|                |  |  |  |  |  |  |  |
|----------------|--|--|--|--|--|--|--|
| Priming        | need to be disinfect with the means to remove algae and fungi by using ALGHESIL. In the case of new cement plasters there should be min. three weeks of seasoning time.  |  |  |  |  |  |  |
| Application    | Before applying the paint the substrate should be primed using SEMPRE GRUNT W or LATEX GRUNT, LATEX GRUNT PREMIUM. Extra-absorbent substrates need to be primed twice using the "wet on wet" method.   |  |  |  |  |  |  |
|                | Apply twice using a roller, brush, or spray (including AIRLESS; application parameters are in the table). After opening the package, check the lid for any dried paint residue resulting from improper storage. Their presence in the product may adversely affect the appearance of the coating. If it is necessary to use materials from different production batches on a single architectural element, mix them, e.g., in a container capable of holding several buckets of paint. To avoid color differences, separate architectural elements should be applied in a single work cycle. It is recommended to work at a temperature between +10 and +25°C. Remove the masking tape immediately after painting, before the paint dries. |  |  |  |  |  |  |
| Dilution       | The product is ready for use. If necessary, dilute with water in the amount of maximum 5%. Too much dilution can affect the durability of cover, which results in the appearance of discolouration.  |  |  |  |  |  |  |
| Drying         | At 20°C and a relative air humidity of 55% the drying time of the coating is approx. 2 hours. Low temperatures and increased humidity extend the drying time.  |  |  |  |  |  |  |
| Cleaning tools | Water – directly after use.  |  |  |  |  |  |  |

## PACKING

2,5 l, 5 L, 10 L (white); 2,25 L, 4,5 L, 9 L (colour bases)

## STORAGE

Store the product in original, unopened container, in a cool, but frost-free place. The product is not suitable for use after freezing. Expiry date is located on the lid of the container.

## SAFETY AND HYGENCE OF WORK/ FIRE PROTECTION

Keep out of reach of children. Non-inflammable. It is not classified as dangerous under current law. While working maintain basic health and safety rules. In case of contact with eyes rinse with water and seek medical advice immediately. Use only according to purpose. During and after use of the product the room should be ventilated. The room is suitable for use after disappearance of characteristic smell.

**The manufacturer guarantees the product quality, but shall not be liable in terms of its use. The information herein provided is based on the manufacturer's knowledge resulting from many years of observations. This information cannot however replace professional know-how of the contractor and does not exempt the contractor from complying with the rules of the building art and the safety and hygiene at work, thus do not constitute any legal grounds for the settlement of disputes in court. For further questions or doubts, please contact the manufacturer.**