

INTERPROTEKT

acrylic paneling varnish

Sempre[®]

PROPERTIES:

- Ecological
- Odorless
- Water-soluble
- Resistant to washing and scrubbing
- Creates a colorless coating

APPLICATION

Acrylic interior varnish for use on new, absorbent substrates not previously protected with coating products, including absorbent, seasoned substrates such as concrete, brick, stone, and those coated with plaster (TESORO, MARESIL, PROGRESIL, AZURO), acrylic and latex paints with a scrub resistance class of 1 or 2 according to EN-13300, and decorative products (SEMPRE PREMIO). Designed for decorative and protective coatings in residential, office, and restaurant spaces, among others. It provides environmentally friendly, easy-to-clean protection.

TECHNICAL DATA

Group of products	Products for interior
Contains	acrylic dispersion, water, preservatives, additives.
Colors	Colorless - transparent
Coating appearance	Matt, satin, gloss
Consumption	ca. 0,07 l/m ² for single painting, depending on the absorbency of the substrate *

PARAMETERS	Parameter	Norm	Value	Unit
	Density	EN ISO 2811-1:2023	1,05 ± 0,05	g/cm ³
	Appearance of the coating / specular gloss determined at a measurement angle of: 60° (gloss, satin) 85° (matte)	EN 13300:2022	Gloss: 60 – 70 (G1) Satin: 25 – 35 (G2a) Matte: 5 – 10 (G3)	---
	Largest grain size (granularity)	EN 13300:2022	S1 (fine - ≤100)	µm
	Wet scrub resistance (at 200 scrubs)	EN 13300:2022	Class R1 (≤ 5)	µm
	Hiding power	EN 13300:2022	Transparent product	-
	VOC content limit according to Directive 2004/42 /EC for this product: Cat. A/e/WB limit value: 130 g/l. This product contains max 130 g/l			

The values stated are average values obtained during testing. Due to the use of natural resources actual values may differ slightly from those listed in the table.

* Consumption is dependent on substrate and application technique. The stated value is an estimate.

USE INSTRUCTION

Substrates	Typical construction substrate should be dry, clean, firm, sound, even and free of grease.
Priming	This product is intended for application over existing plaster, paint, or other decorative coatings. Primer is not required.
Application	NOTE: Before application, it is essential to test the adhesion of the INTERPROTEKT varnish to the substrate. It is essential that the existing paint coating has a wet scrub resistance of at least Class 2 according to EN 13300.
Dilution	Stir thoroughly before use. Apply two evenly thick coats, one at a time, over the entire surface from edge to edge to avoid dry cuts. Applying the product with a brush may result in varying degrees of transparency. It is recommended to work at temperatures between +5 and +30°C.
Drying	The product is ready for use, does not require dilution.
Cleaning tools	At 20°C and a relative air humidity of 55% the drying time of the coating is approx. 2 hours. Low temperatures and increased humidity extend the drying time.
Cleaning tools	Water – directly after use.

PACKING

1 l, 5 L

STORAGE

Store the product in original, unopened container, in a cool, but frost-free place. The product is not suitable for use after freezing. Expiry date is located on the lid of the container.

SAFETY AND HYGENE OF WORK/ FIRE PROTECTION

Keep out of reach of children. Non-inflammable. It is not classified as dangerous under current law. While working maintain basic health and safety rules. In case of contact with eyes rinse with water and seek medical advice immediately. Use only according to purpose. During and after use of the product the room should be ventilated. The room is suitable for use after disappearance of characteristic smell.

The manufacturer guarantees the product quality, but shall not be liable in terms of its use. The information herein provided is based on the manufacturer's knowledge resulting from many years of observations. This information cannot however replace professional know-how of the contractor and does not exempt the contractor from complying with the rules of the building art and the safety and hygiene at work, thus do not constitute any legal grounds for the settlement of disputes in court. For further questions or doubts, please contact the manufacturer.