

DECLARATION OF PERFORMANCE No. EPS/ DoP-31/ 2026

1. Unique identification code of the product-type:

SEMPRE TERM GRAFITE EPS 031

2. Intended use/es: **Thermal insulation in construction**

3. Manufacturer: **SEMPRE FARBY Sp. z o.o., ul. gen.J. Kuźtronia 60, 43 – 301 Bielsko – Biała**

4. Authorised representative: **NPD**

5. System/s of AVCP: **SYSTEM 3**

6a. Harmonised standard:

EN-13163: 2012 + A1:2015

Notified body/ies:

No. 1020 - Technical and Test Institute for Construction Prague, S0E,

6b. European Assessment Document:

European Technical Assessment: **NPD**

Technical Assessment Body: **NPD**

Notified body/ies: **NPD**

7. Declared performance/s:

Essential characteristic	Declared values		Harmonized technical specification
Thermal resistance	Thermal resistance and thermal conductivity	$R_D \geq$ values in Table 2 $\lambda_D \leq 0,031 \text{ W/m}\cdot\text{K}$	EN 13163:2012+ A1:2015
	Thickness	10 – 300 mm T(2) (± 2 mm)	
Reaction to fire	Reaction to fire	E, E _{fl}	
Durability of reaction to fire against heat, weathering, ageing/ degradation	Durability characteristic	E, E _{fl}	
Durability Of thermal resistance against heat, weathering, ageing/ degradation	Thermal resistance and thermal conductivity	$R_D \geq$ values in Table 2 $\lambda_D \leq 0,031 \text{ W/m}\cdot\text{K}$	
	Durability characteristic	no property changes	
Compressive strenght	Compressive stress or compressive strenght	CS (10)50 ($\geq 50 \text{ kPa}$)	
Tensile/ Flexural strenght	Bending strenght	BS 100 ($\geq 100 \text{ kPa}$)	
	Tensile strenght perpendicular to faces	TR 100 ($\geq 100 \text{ kPa}$)	

Durability of compressive strenght against ageing, degradation	Compressive creep	NPD
	Freeze-thaw resistance	
	Long term thickness reduction	
Water permeability	Long term water absorption or by immersion	NPD
	Long term water absorption by diffusion	
Water vapour permeabiity	Water vapour transmission	NPD
Impact noise transmission nindex (for floors)	Dynamic stiffness	NPD
	Thickness d _L	
	Compressibility,	
Continuous glowing combustion	Continuous glowing combustion	NPD
Release of dangerous substances to the indoor environment	Release of dangerous substances	NPD

EN 13163:2012+ A1:2015

Table no. 2. Thermal resistance

Thickness of board, [mm]	10	20	30	40	50	60	70	80	90	100	110	120	130	140
Thermal resistance R [m ² ·K/W]	0,30	0,60	0,95	1,25	1,60	1,90	2,25	2,55	2,90	3,20	3,50	3,85	4,10	4,50
Thickness of board, [mm]	150	160	170	180	190	200	210	220	230	240	250	260	270	280
Thermal resistance R [m ² ·K/W]	4,80	5,15	5,45	5,80	6,10	6,45	6,75	7,05	7,40	7,70	8,05	8,35	8,70	9,00
Thickness of board, [mm]	290	300												
Thermal resistance R [m ² ·K/W]	9,35	9,65												

8. Appropriate Technical Documentation and/or Specific Technical Documentation: **NPD**

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

KIEROWNIK LABORATORIUM
mgr Aleksandra Drózd

[Name]

at Bielsko – Biała on 19.01.2026