

DECLARATION OF PERFORMANCE No FOLIA/ DoP-02/2025

1. Unique identification code of the product-type:

WATERPROOFING MEMBRANE

2. Intended use/es:

all external and internal installations and swimming pools beneath ceramic tiling

3. Manufacturer: SEMPRE FARBY Sp. z o.o., ul. gen.J. Kustronia 60, 43 – 301 Bielsko – Biała

4. Authorised representative: NPD

5. System/s of AVCP:

Water tightness – SYSTEM 3 The remaining - SYSTEM 4

6a. Harmonised standard: EN-14891:2012

Notified body/ies: : Łukasiewicz Instytut Ceramiki i Materiałów Budowlanych - 1487

6b. European Assessment Document: European Technical Assessment: **NPD** Technical Assessment Body: **NPD**

Notified body/ies: NPD

7. Declared performance/s:

Essential characteristics		Requirement	Harmonised technical specification
Initial tensile adhesion strenght		≥ 0,5 N/mm²	
Water tightness	Waterproofing	no penetration	
Crack bridging ability under standard conditions		≥ 0,75 mm	1
Durability of initial tensile adhesion against heat ageing action	Tensile adhesion strenght after heat ageing	≥ 0,5 N/mm²	EN 14891: 2012
Durability of initial tensile adhesion against water	Tensile adhesion strenght after water contact	≥ 0,5 N/mm²	
Durability of initial tensile adhesion against contact with limer water	Tensile adhesion strenght after contact with lime water	≥ 0,5 N/mm²	
Durability of initial tensile adhesion against freeze and freeze-thaw cycles	Tensile adhesion strenght after freeze-thaw cycles	≥ 0,5 N/mm²	
Release of dangerous substances		NPD	

FOLIA/DoP-02/ 2025



8. Appropriate Technical Documentation and/or Specific Technical Documentation:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



[Name]

at Bielsko - Biała on 11.06.2025.

SEMPRE FARBY Sp. z o.o.